



PRODUCT:	ArmorCore Pro with UltraTec Construction
Construction:	Matte Vinyl Resin Composition
Wearlayer:	High Density Vinyl Foam
Cushion:	Fibrous Felt Inner Layer and Dense Flexible Vinyl Composite Backing
Backing:	
Applicable Specifications:	ASTM, F1303, Type I, Gr. 3, Class B
Indoor Air Quality:	FloorScore Certified CHPS 01350 Certified
National Green Building Standard ICC 700-2008:	Meets
LEED MR5.0 Regional Materials:	Meets Guidelines
LEED EQ4.3 Certified Low Emitting Product:	Meets Guidelines
LEED EQ4.1 Certified Low Emitting Adhesive:	Meets Guidelines
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648 > 0.45w/cm²):	Yes
Meets or Exceeds FHA /HUD Minimum Property Standards:	Yes
Slip Resistance:	Meets ADA Recommendations
Width:	6 and 12 Feet
Packaging:	40-130 S.Y. (6') and 80-170 S.Y. (12')
Shipping Weight per Unit:	2.9 lbs. per S.Y.
Shipping Weight per Package:	230 lbs. avg. (6') and 460 lbs. avg. (12')
Warranty Coverage:	ArmorCore 5 Year Residential Limited Warranty Plus 5 year No Buckle warranty
Installation Method:	Your Choice Plus Fully Adhere, Perimeter Fasten or Loose Lay over Approved Wood, Concrete and Qualifying Existing Resilient Floors
Subfloor Application:	All grade levels
Adhesive:	UnderFlor® AS01 Adhesive or QS120 QuikStik Tape
Porous and Non-Porous Surfaces:	Applicator: ¼" Nap Paint Roller
Adhesive Coverage:	300 to 350 sq. ft. per gallon
Optional Fully Adhere Application Porous Surfaces Only:	Trowel Size: 1/16" wide, 1/32" deep, 1/32" apart
Adhesive Coverage:	200 to 250 sq. ft. per gallon
Seam Sealer:	Congoleum SU80 or SU92
Suggested Usage:	
Residential:	Excellent

Finished product manufactured in the United States.